

....."ECTECUG'O GO DTCPG'4"

- fiberglass reinforced plastic pressure vessels series 300 E-4, D.75" direct connection, white painted, UVA-ray proof material;
- end-cap in PP + 30% FG material;
- max operating pressure 300 psi (21 bar);
- connection permeate ½" BSPP female;
- straps and saddles to buy separately

REF.	MODEL	ELEMENTS	L (mm)	CONNECTIONS FEED / CONCENTRATE
DE607	300 E – 4014	1 x 14"	461	½" BSPP female
DE608	300 E – 4021	1 x 21"	639	½" BSPP female
DE600	300 E – 4 – 1	1 x 40"	1121	½" BSPP female
DE601	300 E – 4 – 1	1 x 40"	1121	¾" BSPP female
DE602	300 E – 4 – 2	2 x 40"	2137	½" BSPP female
DE603	300 E – 4 – 2	2 x 40"	2137	¾" BSPP female
DE604	300 E – 4 – 3	3 x 40"	3153	½" BSPP female
DE605	300 E – 4 – 3	3 x 40"	3153	¾" BSPP female
DE606	300 E – 4 – 4	4 x 40"	4169	½" BSPP female
DE609	300 E – 4 – 4	4 x 40"	4169	¾" BSPP female

SPARE PARTS:

ITEM	REF.	DESCRIPTION	MATERIAL
2	DE613	Baffle	AISI 316 L
3	DE614	Head ½" BSPP	PP + 30% FG
3	DE618	Head ¾" BSPP	PP + 30% FG
4	DE615	Head seal	EPDM
5	DE611	Saddle	Polyurethane
6	DE616	Adapter seal	EPDM
9	DE612	Strap assembly	AISI 304
11	DE617	Allen screw	AISI 316

CARCASE MEMBRANE 4"

